Global tender notification for the procurement of Vibration-Isolated Optical Table

(GTE Approval Number: IISC-GTE-2023-324)

Tender Summary

1	Section 1	Bid Schedule			
2	Section 2	Eligibility Criteria	As specified by IISc		
3	Section 3	Terms and Conditions	As specified by IISc		
4	Section 4	Specifications	Technical Specifications		
5	Section 5	Technical Bid	Annexure 1: Bidder details		
			Annexure 2: Declaration regarding the		
			experience of the bidder		
			Annexure 3: Declaration of track record		
			Annexure 4: Declaration of acceptance of terms		
			and conditions		
			Annexure 5: Details of items quoted.		
6	Section 6	Commercial Bid	Quotation with price, and technical		
			specifications of the equipment.		

	-	
1	Tender Number	IPC/SG/2024/OT-1
2	Tender Date	15 th March 2024
3	Item Description	Vibration-isolated Optical Table
4	Tender Type	Two bid system:
		(a) Technical Bid (Part A)
		(b) Commercial Bid (part B)
5	Place of tender submission	The Chairperson
		Kind attention: Dr. Soumen Ghosh
		Department of Inorganic and Physical Chemistry
		Indian Institute of Science
		Bengaluru, Karnataka 560012, India
6	Last Date and Time for	8 th April 2024, 5:00 PM (Indian Standard Time)
	tender submission	
7	Primary Point of Contact	Dr. Soumen Ghosh
		Department of Inorganic and Physical Chemistry,
		Indian Institute of Science, Bengaluru 560012, India
		Email: soumenghosh@iisc.ac.in

Section 1: Bid Schedule

This is a Request for quote (RFQ) from the **Original Equipment Manufacturer (OEM) or their authorized Indian distributor** for the procurement of a "Vibration-isolated Optical Table" at the Department of Inorganic and Physical Chemistry (IPC) in the Indian Institute of Science, Bangalore. All interested vendors shall submit a response demonstrating their capabilities to produce the requested equipment to the primary point of contact.

Section 2: Eligibility Criteria

Prequalification criteria:

- 1. The bidder should sign and submit the declaration for Acceptance of Terms and Conditions as per -Annexure 4.
- 2. The Bidder must not be blacklisted/banned/suspended or have a record of any service-related dispute with any organization in India or elsewhere. A declaration to this effect has to be given as per Annexure 3.
- 3. System Catalogue should be produced with the Technical Bid. Original Invoice, Original Warranty Certificate, and Original Test Reports should be produced for all imported items from OEM (Original Equipment Manufacturer) at the time of supply of equipment.
- 4. Manufacturers should have ISO or equivalent international standard certificate. Please attach the required certificate with the bid.
- 5. The supplier will support the user with all the spares for a minimum period of 5 years.
- 6. Details of experienced service engineers including contact detail should be provided in the tender document.
- 7. Bidder shall have to submit audited accounts (Balance sheet profit and loss account) for financial year 2019-20, 2020-21 and 2021-22. The audited statement must be signed and stamped by qualified chartered accountants. The supplier will support the user with all the spares for a minimum period of 5 years.
- 8. Bidder must submit Income Tax return for assessment years 2020-21, 2021-22 and 2022-23.
- 9. The Bidder should have supplied similar equipment in atleast 10 Central Universities preferably in centrally Funded Technical Institutes (IITs, IISc, IISER, NIT). Please provide the details and contact information.

Section 3: Terms and conditions

(A) Submission of Tender

- 1. All documentation in the tender should be in English.
- 2. Vendors will be required to submit a technical proposal and a commercial proposal in two separate sealed envelopes (two bid systems). The technical bid should contain all commercial terms and conditions, except the price. Only vendors who meet the technical requirement will be considered for the commercial negotiation.
- 3. **The technical bid** (Part A) must contain a point-by-point technical compliance document. The technical proposal should contain a compliance table with 5 columns.

a. The first column must list the technical requirements, in the order that they are given in the technical requirements below.

b. The second column must provide the specification of the instrument against the requirement (please provide quantitative responses wherever possible)

c. The third column should describe the compliance with a "YES" or "NO" only. Ensure that the entries in column 2 and column 3 are consistent.

d. The fourth column should clearly state the reasons/explanations/context for deviations if any.

e. The fifth column may contain additional remarks. It can be used to highlight the technical features, qualify the response of previous columns, or provide additional details.

- 4. The commercial bid (Part B) Indicating item-wise price for the items mentioned in the technical bid, as per the format of quotation provided in the tender, and other commercial terms and conditions. The commercial bid should indicate the following separately: (a) equipment price (b) optional items (c) Shipping cost and (d) the Total cost.
- 5. The technical bid and price bid should each be placed in separate sealed covers, superscribing on both the envelopes the tender no. and the due date. Both these sealed covers are to be placed in a bigger cover which should also be sealed and duly superscripted with the Tender No, Tender Description & Due Date.
- 6. The SEALED COVER superscribing tender number / due date & should reach the Chairperson Office, Department of Inorganic and Physical Chemistry, Indian Institute of Science, Bangalore 560012, India on or before the due date mentioned in the tender notice. In case the due date happens to be a holiday the tender will be accepted and opened on the next working day. If the quotation cover is not sealed, it will be rejected.
- 7. All queries are to be addressed to the person identified in "Section 1: Bid Schedule" of the tender notice.

- 8. GST/other taxes, levies etc., are to be indicated separately. The BIDDER should mention GST Registration and PAN in the tender document (Indian Bidders only).
- 9. In addition to that listed in the technical table that the vendor would like to bring to the attention of the committee, such as data sheets, technical plots etc. must be listed at the end of the compliance table. The committee will go though the data provided and those available in their website to evaluate the suitability.
- 10. The decision of the purchase committee will be final. The Institute reserves the right to accept or reject any bid or to annul the bidding process and reject all bids, at any time before the award of the contract without thereby incurring any liability of the affected bidder or bidders.

(B) Cancellation of Tender

Notwithstanding anything specified in this tender document, IISc Bangalore, in its sole discretion, unconditionally and without having to assign any reason, reserves the rights:

- a. To accept OR reject the lowest tender or any other tender or all the tenders.
- b. To accept any tender in full or in part.
- c. To reject the tender, offer not confirming to the tender terms.

(C) Validity of the Offer

The offer shall be valid at least 60 Days from the date of opening of the commercial bid.

(D) Evaluation of the Offer

- 1. The technical bid (Part A) will be opened first and evaluated.
- 2. Bidders meeting the required eligibility criteria as stated in Section 2 of this document shall only be considered for Commercial Bid (Part B) opening. Further, agencies not furnishing the documentary evidence as required will not be considered.
- 3. Pre-qualification of the bidders shall not imply final acceptance of the Commercial Bid. The agency may be rejected at any point during technical evaluation or commercial evaluation. The decision regarding acceptance and/or rejection of any offer in part or full shall be the sole discretion of IISc Bangalore, and the decision in this regard shall be binding on the bidders.
- 4. The award of the contract will be subject to acceptance of the terms and conditions stated in this tender.
- 5. Any offer which deviates from the vital conditions (as illustrated below) of the tender is liable to be rejected:

a. Non-submission of complete offers.

b. Receipt of bids after the due date and time and or by email/fax (unless specified otherwise).

- c. Receipt of bids in open conditions.
- 6. In case any BIDDER is silent on any clauses mentioned in these tender documents, IISc Bangalore shall consider that the BIDDER had accepted the clauses as of the tender and no further claim will be entertained.
- 7. No revision in the terms and conditions quoted in the offer will be entertained after the last date and time fixed for receipt of tenders.
- 8. The lowest bid will be calculated based on the total price of all items tendered for Basic equipment along with accessories selected for installation, operation, preprocessing and post-processing, optional items, recommended spares, warranty, and annual maintenance contract.

(E) Pre-requisites:

The bidder will provide the prerequisite installation requirement of the equipment along with the technical bid.

(F) Warranty:

The complete system is to be under a warranty period of **a minimum of 1 year** from the date of delivery, including a free supply of consumables and spare parts and online assistance for 3 subsequent years. If the instrument is found to be defective, it must be replaced or rectified at the cost of the bidder within 30 days from the date of receipt of written communications from IISc Bangalore. If there is any delay in replacement or rectification, the warranty period should be correspondingly extended.

(G) Purchase Order:

- 1. The order will be placed on the bidder whose bid is accepted by IISc based on the terms & conditions mentioned in the tender document.
- 2. The quantity of the items in the tender is only indicative. IISc, Bangalore reserves the right to increase /decrease the quantity of the items depending on the requirement.
- 3. If the quality of the product and service provided is not found satisfactory, IISc Bangalore reserves the right to cancel or amend the contract.

(H) Delivery and Installation

The bidder shall provide the lead time to delivery, installation and made functional at IISc Bangalore from the date of receipt of the purchase order. The system should be delivered, installed, and made functional **within 140 days** from the date of receipt of the purchase order. The supply of the items will be considered as effected only on satisfactory installation and inspection of the system and inspection of all the items and features/capabilities tested by the IISc, Bangalore. After successful installation and inspection, the date of taking over the entire

system by the IISc, Bangalore shall be taken as the start of the warranty period. No partial shipment is allowed. The technical installation personnel/engineer, who will perform the installation, must possess proof of a training certificate from the manufacturing company/factory/principal, which should be submitted along with the tender offer.

(I) Payment Terms:

100% payments (except AMC) will be released after completion of delivery and satisfactory installation subject to TDS as per rules. AMC cost (if ordered), after completion of the warranty period) will be released on a half-yearly basis at the end of each six months subject to satisfactory services. The AMC will be comprehensive. As per GFR, no advance payment can be made to the authorized Indian distributors unless an equal amount of bank guarantee is provided.

(J) Statutory Variation:

Any statutory increase in the taxes and duties after the bidder's offer, if it takes place within the original contractual delivery date, will be borne by IISc, Bangalore subject to the claim being supported by documentary evidence. However, if any decrease takes place the advantage will have to be passed onto IISc, Bangalore.

(K) Disputes and Jurisdiction:

Any legal disputes arising out of any breach of contract about this tender shall be settled in the court of competent jurisdiction located within the city of Bangalore, India.

(L) General:

- 1. All amendments, time extensions, clarifications etc., within the period of submission of the tender will be communicated electronically. No extension in the bid due date/time shall be considered on account of delay in receipt of any document(s) by mail.
- 2. The bidder may furnish any additional information, which is necessary to establish capabilities to complete the envisaged work. It is, however, advised not to furnish superfluous information.
- 3. The bidder may visit the installation site before submission of the tender, with prior intimation.
- 4. Any information furnished by the bidder found to be incorrect, either immediately or at a later date, would render the bidder liable to be debarred from tendering/taking up of work in IISc Bangalore.

Section 4: Technical Specifications

Technical Specification for Vibration-isolated Optical Table

degree of vibration isolation and active levelling for hosting very sensitive optical experiments with a coupler for an upgrade. the future. 2 Table Dimensions: Width: (W) 1500 mm (L) 3600 mm & Thickness ≥305 mm and to be coupled as L shape in future. Top Dimensions: 1500x3600 mm Thickness: ≥305 mm	Sr.	Description	Unit	Specifications
active levelling for hosting very sensitive optical experiments with a coupler for an upgrade. 7 2 Table Dimensions: Width: (W) 1500 mm & Thickness: ≥305 mm and to be coupled as L shape in future. 7 3 Coupler for L-shape 4 Mounting holes mm 5 Mounting holes borders mm 5 Mounting Surface mm 6 Working Surface mm 7 Core design 8 Deflection in the presence of mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic or non-magnetic can be magnetic or not-magnetic can be magnetic o	1	Optical table system with a high	1	To be upgraded to an L shape for
sensitive optical experiments with a coupler for an upgrade. 7 2 Table Dimensions: Width: (W) 1500 mm (L) 3600 mm & Thickness ≥305 mm and to be coupled as L shape in future. 7 3 Coupler for L-shape 4 Mounting holes mm 5 Mounting holes borders mm 5 Mounting holes borders mm 6 Working Surface mm 7 Core design 8 Deflection in the presence of across the table (maximum relative motion) 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm coefficient 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface 400 series ferromagnetic stainless steel		degree of vibration isolation and		the future.
with a coupler for an upgrade. 7 2 Table Dimensions: Width: (W) 1500 mm (L) 3600 mm & Thickness ≥305 mm and to be coupled as L shape in future. 7 3 Coupler for L-shape 4 Mounting holes mm 5 Mounting holes borders mm 6 Working Surface mm 7 Core design 8 Deflection in the presence of mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic or non-magnet		active levelling for hosting very		
2 Table Dimensions: Width: (W) 1500 mm (L) 3600 mm & Thickness ≥305 mm and to be coupled as L shape in future. Top Dimensions: 1500x3600 mm Thickness: ≥305mm 3 Coupler for L-shape Necessary internal coupler to be quoted. 4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm cores the table (maximum relative motion) 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity.		sensitive optical experiments		
1500 mm (L) 3600 mm & Thickness ≥305 mm and to be coupled as L shape in future. Thickness: ≥305 mm 3 Coupler for L-shape 4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm close to or better than 1x10 ⁻⁶ mm across the table (maximum relative motion) 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx.5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. To indese the point loading capacity.		with a coupler for an upgrade.		
Thickness ≥305 mm and to be coupled as L shape in future. 3 Coupler for L-shape 4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness: 0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻⁶ mm across the table (maximum relative motion) 9 Maximum dynamic deflection Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity.	2	Table Dimensions: Width: (W)	mm	-
coupled as L shape in future. Necessary internal coupler to be quoted. Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm Mounting holes borders mm Less than 10 to 15 mm from the table border Mounting surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic Core design Honeycomb structure Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm coefficient Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 0.8x10 ⁻³ Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ Surface flatness mm ±0.1 mm over 600 mm square Top and bottom plates thickness mm Approx.5 mm Maxing surface 400 series ferromagnetic stainless steel Table core interface To increase the point loading capacity.		1500 mm (L) 3600 mm &		Thickness: ≥305mm
3 Coupler for L-shape Necessary internal coupler to be quoted. 4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm load 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm square 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are		Thickness \geq 305 mm and to be		
4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm load 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity.		coupled as L shape in future.		
4 Mounting holes mm Metric M6 holes with numbered grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 0.8x10 ⁻³ 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are	3	Coupler for L-shape		Necessary internal coupler to be
grid labels. The separation between the mounting holes:25 mm 5 Mounting holes borders mm 6 Working Surface mm 7 Core design 8 Deflection in the presence of load mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ mm 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity.				*
between the mounting holes:25 5 Mounting holes borders 6 Working Surface 7 Core design 7 Core design 8 Deflection in the presence of load 9 Maximum linear vibration level across the table (maximum relative motion) 10 Maximum dynamic deflection 11 Surface flatness 12 Top and bottom plates thickness 13 Working surface 14 Triple core interface 14 Triple core interface 15 Grid Labeling	4	Mounting holes	mm	Metric M6 holes with numbered
mm mm 5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 0.8x10 ⁻³ 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				grid labels. The separation
5 Mounting holes borders mm Less than 10 to 15 mm from the table border 6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				between the mounting holes:25
6 Working Surface mm Flat stainless-steel surface (flatness:0.1-0.2mm) (Material can be magnetic or non-magnetic 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				
6 Working Surface mm Flat stainless-steel surface 7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are	5	Mounting holes borders	mm	
7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				
Core designHoneycomb structure8Deflection in the presence of loadmmClose to or better than 1x10 ⁻³ mm9Maximum linear vibration level across the table (maximum relative motion)mmClose to or better than 1x10 ⁻⁶ mm10Maximum dynamic deflection coefficientClose to or better than 0.8x10 ⁻³ 11Surface flatnessmm±0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are	6	Working Surface	mm	
7 Core design Honeycomb structure 8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				
8 Deflection in the presence of load mm Close to or better than 1x10 ⁻³ mm 9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				
loadmmClose to or better than 1x10-6 mm9Maximum linear vibration level across the table (maximum relative motion)mmClose to or better than 1x10-6 mm10Maximum dynamic deflection coefficientClose to or better than 0.8x10-311Surface flatnessmm±0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are				
9 Maximum linear vibration level across the table (maximum relative motion) mm Close to or better than 1x10 ⁻⁶ mm 10 Maximum dynamic deflection coefficient Close to or better than 0.8x10 ⁻³ 11 Surface flatness mm ±0.1 mm over 600 mm square 12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are	8	_	mm	Close to or better than 1×10^{-3} mm
across the table (maximum relative motion)across the table (maximum relative motion)10Maximum dynamic deflection coefficientClose to or better than 0.8×10^{-3} 11Surface flatnessmm ± 0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are				
relative motion)Close to or better than 0.8×10^{-3} 10Maximum dynamic deflection coefficientClose to or better than 0.8×10^{-3} 11Surface flatnessmm ± 0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are	9		mm	Close to or better than 1×10^{-6} mm
10Maximum dynamic deflection coefficientClose to or better than 0.8×10^{-3} 11Surface flatnessmm $\pm 0.1 \text{ mm over } 600 \text{ mm square}$ 12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are				
coefficientmm±0.1 mm over 600 mm square11Surface flatnessmm±0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are				
11Surface flatnessmm±0.1 mm over 600 mm square12Top and bottom plates thicknessmmApprox. 5 mm13Working surface400 series ferromagnetic stainless steel14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are	10	-		Close to or better than 0.8×10^{-3}
12 Top and bottom plates thickness mm Approx. 5 mm 13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are				
13 Working surface 400 series ferromagnetic stainless steel 14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are			mm	-
14 Triple core interface To increase the point loading capacity. 15 Grid Labeling Alpha-numeric grid labels are			mm	
14Triple core interfaceTo increase the point loading capacity.15Grid LabelingAlpha-numeric grid labels are	13	Working surface		C
Image: Constraint of the second se				
15 Grid Labeling Alpha-numeric grid labels are	14	Triple core interface		r e
required.	15	Grid Labeling		1 0
				-
16IsolationPneumatic vibration isolation and	16	Isolation		
				actively adjustable levelling of the Page 8 of 17

IntermediationIntermediation17Damping17Damping17Damping17Damping17Damping17Damping17Damping18Isolator Heightsmm19Self-Centering19Self-Centering20Height Adjustmentsmm21Settling Timesec22Levelling Indicator23Hybrid Chamber Design24Load capacity per isolatorkg25Re-levelling accuracymm26Horizontal/Vertical Isolation27Air CompressordB28Tank capacityItr29Release Value Sound Leveldb29Release Value Sound Leveldb20Hads free operator of the ereglacements, a separate quote should be provided for additional replacements, a separate quote should be provided for additional replacements, a separate quote should be provided for additional riperational filters				tables. Free from acoustic
damping frequency region from 1.5 Hz-500 Hz.17DampingConstrained layer core damped working surface and composite edge finish. Broadband damping along with tuned damping. Broadband damping along with tuned damping. Broadband damping dong with tuned damping.18Isolator Heightsmm~600 mm19Self-CenteringSelf-centring design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 tr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters<				
Image: section of the section of th				-
17DampingConstrained layer core damped working surface and composite edge finish. Broadband damping along with tuned damping. Broadband damping along with tuned damping.18Isolator Heightsmm~600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				
NoteNoteNote18Isolator Heightsmm~600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolator kgkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersAutomated.32Hands free operator of the endAutomated.	17	Damping		
edge finish. Broadband damping along with tuned damping. Broadband damping along with tuned damping.18Isolator Heightsmm~600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg-900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of the encessaryAutomated.	17	Damping		•
along with tuned damping. Broadband damping along with tuned damping.18Isolator Heightsmm-600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg-900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				
Broadband damping along with tuned damping.18Isolator Heightsmm~600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg-900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of the encentersAutomated.				
Image: 18Isolator Heightsmm-600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg-900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 thr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of the enverted restAutomated.				0 1 0
18Isolator Heightsmm~600 mm19Self-CenteringSelf-centering design for unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				
19Self-CenteringSelf-centeringdesignfor unrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	10	.		
andunrestricted piston motion is preferred.20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.			mm	
Image: sec	19	Self-Centering		
20Height Adjustmentsmm25 mm to 30 mm21Settling Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				_
21Setting Timesec1.5 sec or less22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				*
22Levelling IndicatorBuilt-in levelling indicators should provide visual feedback ensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	20		mm	25 mm to 30 mm
Image: series of the series	21	_	sec	1.5 sec or less
andensuring the table is properly floating at the correct level.23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	22	Levelling Indicator		Built-in levelling indicators
Image: solution of the second state st				should provide visual feedback
23Hybrid Chamber DesignTo maximize isolation bandwidth and stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 Itr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				ensuring the table is properly
And stability.24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				floating at the correct level.
24Load capacity per isolatorkg~900 kg25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	23	Hybrid Chamber Design		To maximize isolation bandwidth
25Re-levelling accuracymmClose to or better than 0.25 mm26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				and stability.
26Horizontal/Vertical Isolation%Accuracy >95%27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	24	Load capacity per isolator	kg	~900 kg
27Air CompressordBLow-noise compressor for floating table (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	25	Re-levelling accuracy	mm	Close to or better than 0.25 mm
LableLable (should be <30 dB noise). All necessary air filters/regulators and valves should be supplied along with the compressor.28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	26	Horizontal/Vertical Isolation	%	Accuracy >95%
Image: heat set in the set i	27	Air Compressor	dB	Low-noise compressor for floating
28Tank capacityItr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				table (should be <30 dB noise). All
Image: Non-transformed base of the second				necessary air filters/regulators and
28Tank capacityltr3-5 ltr29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				valves should be supplied along
29Release Value Sound LeveldbLess than 6530Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.				with the compressor.
30Maximum Air pressurepsi100 psi31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	28	Tank capacity	ltr	3-5 ltr
31The compressor should include the regulator filter and the air intake filtersIn case of any future required replacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	29	Release Value Sound Level	db	Less than 65
the regulator filter and the air intake filtersreplacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	30	Maximum Air pressure	psi	100 psi
the regulator filter and the air intake filtersreplacements, a separate quote should be provided for additional filters32Hands free operator of theAutomated.	31	The compressor should include	-	_
intake filtersshould be provided for additional filters32Hands free operator of theAutomated.		-		replacements, a separate quote
32 Hands free operator of the Automated.				
32Hands free operator of theAutomated.				-
1	32	Hands free operator of the		Automated.
		-		

Section 5- Technical Bid

The technical bid should furnish all requirements of the tender along with all annexures in this section and submitted to

The Chairperson, Attn. Dr. Soumen Ghosh Department of Inorganic and Physical Chemistry Indian Institute of Science, Bengaluru 560012, India Email: soumenghosh@iisc.ac.in

Annexure-1:

Details of the Bidder

The bidder must provide the following mandatory information & attach supporting documents wherever mentioned:

Details of the Bidder

- Sl. No Items Details
- 1. Name of the Bidder
- 2. Nature of Bidder (Attach attested copy of Certificate of Incorporation/ Partnership Deed)
- 3. Registration No/ Trade License, (attach attested copy)
- 4. Registered Office Address
- 5. Address for communication
- 6. Contact person- Name and Designation
- 7. Telephone No
- 8. Email ID
- 9. Website
- 10. PAN No. (attach copy)
- 11. GST No. (attach copy)

Signature of the Bidder

Name, Designation, Seal

Annexure-2:

Declaration regarding experience

To,

The Chairperson, Department of Inorganic and Physical Chemistry Indian Institute of Science, Bengaluru 560012, India

Ref: Tender No: XXXXXXX

Dated: XXXXX

Supply and installation of Vibration-Isolated Optical Table at the Department of Inorganic and Physical Chemistry in IISc Bangalore.

Sir,

I've carefully gone through the Terms & Conditions contained in the above referred tender. I hereby declare that my company / firm has years of experience in supplying and installing vibration-isolated optical table.

(Signature of the Bidder)

Name, Designation, Seal

Annexure-3:

Declaration of the track record

To,

The Chairperson,

Department of Inorganic and Physical Chemistry

Indian Institute of Science, Bengaluru 560012, India

Ref: Tender No: XXXXXXX

Dated: XXXXX

Supply and installation of Vibration-Isolated Optical Table at the Department of Inorganic and Physical Chemistry in IISc Bangalore.

Sir,

I've carefully gone through the Terms & Conditions contained in the above referred tender. I hereby declare that my company/ firm is not currently debarred /blacklisted by any Government / Semi Government organizations/institutions in India or abroad. I further certify that I'm competent officer in my company/firm to make this declaration.

Or

I declare the following,

ſ	Sl.	Country in which	Blacklisted/debarred by	Reasons	Since when and
	No.	the company is	Government/Semi		for how long
		Debarred/blacklisted	Government/Organizations		
	/case is Pending		/Institutions		

(NOTE: In case the company / firm was blacklisted previously, please provide the details regarding period for which the company / firm was blacklisted and the reason/s for the same). Yours faithfully

(Signature of the Bidder)

Name Designation, Seal

Annexure – 4:

Declaration for acceptance of terms and conditions

To,

The Chairperson, Department of Inorganic and Physical Chemistry Indian Institute of Science, Bengaluru 560012, India

Ref: Tender No: XXXXXXX

Dated: XXXXX

Supply and installation of Vibration-Isolated Optical Table at the Department of Inorganic and Physical Chemistry in IISc Bangalore.

Sir,

I've carefully gone through the Terms & Conditions as mentioned in the above referred tender document. I declare that all the provisions of this tender document are acceptable to my company. I further certify that I'm an authorized signatory of my company and am, therefore, competent to make this declaration.

Yours faithfully,

(Signature of the Bidder)

Name, Designation, Seal

Annexure – 5:

Details of items quoted:

- a. Company Name
- b. Product Name
- c. Part / Catalogue number
- d. Product description / main features
- e. Detailed technical specifications
- f. Remarks

Instructions to bidders:

- 1. Bidder should provide technical specifications of the quoted product/s in detail.
- 2. Bidder should attach product brochures along with technical bid.

3. Bidders should clearly indicate compliance or non-compliance of the technical specifications provided in the tender document.

Section 6 – Commercial Bid

The commercial bid should be furnished with all requirements of the tender with supporting documents as mentioned under:

S.No	Description	Cat. Number	Quantity	Unit Price	Sub total
1.	Essential items noted in the				
	technical specification				
1.a	(details of essential				
	items)				
1.b					
2.	Optional items noted in the				
	technical specification				
2.a	(details of essential				
	items)				
2.b					
3.	Accessories for operation				
	and installation				
4.	All Consumables, spares and				
	software to be supplied				
	locally				
5.	Warranty (1 year)				
6.	Cost of Insurance and				
	Airfreight				
7.	CIP/CIF IISc, Bengaluru				

Any additional items

Sl. No Descri	ption	Cat. Number	Quantity	Unit Price	Sub total

Addressed to

The Chairperson, Attn. Dr. Soumen Ghosh Department of Inorganic and Physical Chemistry Indian Institute of Science, Bengaluru 560012, India

Section 7 – Checklist

(This should be enclosed with technical bid- Part A)

The following items must be checked before the Bid is submitted:

1. Sealed Envelope "A": Technical Bid

1. Section 5- Technical Bid (each page signed by the authorized signatory and sealed) with the below annexures:

- a. Annexure 1: Bidders details
- b. Annexure 2: Declaration regarding experience
- c. Annexure 3: Declaration regarding clean track record
- d. Annexure 4: Declaration for acceptance of terms and conditions
- e. Annexure 5: Details of items quoted

2. Copy of this tender document duly signed by the authorized signatory on every page and sealed.

2. Sealed Envelop "B": Commercial Bid

Section 6: Commercial Bid

Your quotation must be submitted in two envelopes: Technical Bid (Envelope A) and Commercial Bid (Envelope B) super scribing on both the envelopes with Tender No. and due date and both of these in sealed covers and put in a bigger cover which should also be sealed and duly super scribed with Tender No., Tender description & Due Date.